

## HOWTO power cycle slot 4

Ford, Christopher

Mon 10/17/2016 4:17 PM

To: Ford, Christopher <caf@slac.stanford.edu>;

----- Recall: IPMB\_ADDR = 0x80+(logical\_slot\*2) -----

```
[caf@lcls-dev3 ~]$ ssh root@SHM-B084-HP04
root@shm-b084-hp04's password:
sh: /usr/bin/X11/xauth: not found
#
# clia deactivate 0x88 0
```

Pigeon Point Shelf Manager Command Line Interpreter

```
Command issued via IPMB, status = 0 (0x0)
Command executed successfully
#
# clia fru
...
88: FRU # 0
Entity: (0x0, 0x0)
Hot Swap State: M1 (Inactive), Previous: M6 (Deactivation In Progress), Last State Change Cause: Normal State Change (0x0)
Device ID String: " "
...
# clia activate 0x88 0
```

Pigeon Point Shelf Manager Command Line Interpreter

```
Command issued via IPMB, status = 0 (0x0)
Command executed successfully
#
# clia fru
...
88: FRU # 0
Entity: (0xa0, 0x60)
Hot Swap State: M4 (Active), Previous: M3 (Activation In Process), Last State Change Cause: Normal State Change (0x0)
Device ID String: "AMCc"
...
#
```