

Group C Test Setup

4/1/2019 Matt Solt


Introduction and Setup


- Group C now has 2 symmetric metal boxes for testing U Channels - insulated with polystyrene and weather-sealed
- Chiller is cooled with Glycol/Water 50/50
- Humidity sensor connected to arduinos (Thanks Omar) and readout with DAQ laptop
- DO NOT COOL WITHOUT CHECKING HUMIDITY READINGS













Heavy Photon Search @PhotonHeavy · Mar 27

Hello World! My name is the Heavy Photon Search, but you can call me "HPS" for short.

0




111

Follow the HPS Twitter Bot at: https://twitter.com/PhotonHeavy for live updates (plots and warnings)

Stable readings show ~0.5% and ~-3.0% humidity

Humidity Monitoring









Twitter Bot Live Updates


Twitter bot complains if humidity is above threshold or readout is disrupted, and when humidity is back at an acceptable level

Plot humidity every ~ 1 hr (configurable)





- Stable running over weekend.
- Takes ~1-1.5 hr to get down to stable humidity



Future Work

To Do:

- Polyester sheets (protect puncturing of polystyrene), will be arriving today
- Cooling lines (adding exterior valves and trim cooling lines)
 - O This can be done quickly when we know when we're going to put the u-channels in
- Final Cleaning

When we are done testing:

- Figure out what to do with the boxes
- Blow out the glycol/water mixture from the cooling lines, cap them
- Gel packs for transporting the silicon