

PingER on VM: output from make install

```
[root@dhcp-nebula-priv-52-7 pinger-2.0.3]# make install
Making install in sw
make[1]: Entering directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3/sw'
make[2]: Entering directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3/sw'
/bin/sh ../mkinstalldirs /usr/local/bin
/usr/bin/install -c pinger2 /usr/local/bin/pinger2
mkdir -p /usr/local/share/pinger/data
/bin/sh ../mkinstalldirs /usr/local/share/pinger
/usr/bin/install -c -m 644 pinger2.pl /usr/local/share/pinger/pinger2.pl
/usr/bin/install -c -m 644 pinger.xsd /usr/local/share/pinger/pinger.xsd
/usr/bin/install -c -m 644 pinger.xml /usr/local/share/pinger/pinger.xml
/usr/bin/install -c -m 644 dnsV4Cmd.pl /usr/local/share/pinger/dnsV4Cmd.pl
/usr/bin/install -c -m 644 beacons.txt /usr/local/share/pinger/beacons.txt
/usr/bin/install -c -m 644 installCron.pl /usr/local/share/pinger/installCron.pl
make install-data-hook
make[3]: Entering directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3/sw'
chmod ugo+x /usr/local/share/pinger/installCron.pl
chmod ugo+x /usr/local/share/pinger/dnsV4Cmd.pl
make[3]: Leaving directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3/sw'
make[2]: Leaving directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3/sw'
make[1]: Leaving directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3/sw'
Making install in docs
make[1]: Entering directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3/docs'
make[2]: Entering directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3/docs'
make[2]: Nothing to be done for `install-exec-am'.
/bin/sh ../mkinstalldirs /usr/local/man/man1
mkdir -p -- /usr/local/man/man1
/usr/bin/install -c -m 644 ./pinger2.1 /usr/local/man/man1/pinger2.1
/bin/sh ../mkinstalldirs /usr/local/share/pinger
/usr/bin/install -c -m 644 pinger2.html /usr/local/share/pinger/pinger2.html
make[2]: Leaving directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3/docs'
make[1]: Leaving directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3/docs'
make[1]: Entering directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3'
make[2]: Entering directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3'
make[1]: Leaving directory `/afs/slac.stanford.edu/u/sf/cottrell/pinger-2.0.3'
[root@dhcp-nebula-priv-52-7 pinger-2.0.3]#
```