

Experiment monitoring tool

Dan Higley suggested to re-implement SXR/AMO detector monitoring tool in order to make it more flexible for switching between experiments.

Dataset

Dan's description refers to LO59 experiment that is sxro5916, i.e.run10 has:

DetInfo and BldInfo keys for sxro5916 run 10

```
cfg.keys:  
XXX: SxrBeamline.0:Opall1000.1  
XXX: SxrEndstation.0:USDUSB.0  
XXX: SxrEndstation.0:Acqiris.1  
XXX: EpicsArch.0:NoDevice.80  
XXX: SxrEndstation.0:Andor.0  
XXX: SxrEndstation.0:USDUSB.1  
XXX: EpicsArch.0:NoDevice.0  
XXX: NoDetector.0:Evr.0  
XXX: NoDetector.0:Evr.1  
XXX: SxrEndstation.0:Acqiris.2  
evt0.keys:  
XXX: FEEGasDetEnergy  
XXX: PhaseCavity  
XXX: EBeam  
XXX: GMD
```

References

- [2016-11-21-DanHigley-online_monitoring.pdf](#) - description of current tool
- [2016-11-22-DanHigley-sxr-mon-tool.txt](#) - e-mail from Dan Higley explaining what he expects from monitoring tool.
- [Experiment Monitor](#) - instructions of how to run application `emon`