p19-0 ring tubes side up anatomy


Table of Conents

- p19-0 ring tubes up interactive map
- Screenshots from the Loading layers of the Interactive Map
- Observations, properties, and measurements by Heater ID
 - Properties
 - Quads
 - Triplets
 - Heater visual inspection
 - Quads
 - Loading experience
 - Quads
 - Triplets
 - Metrology
 - Thermal imaging

p19-0 ring tubes up interactive map

Welcome to the interactive map of the first thermomechanical ring prototype at SLAC. You can visit the Cooling Tubes Down map here.


To explore the ring map in interactive mode, use the buttons within the Gliffy diagram macro in the table on the left. **You may need to enter full screen**. Hover your mouse over the image to get the full screen menu option. Please note that the CMM measurements seem to take an especially long time to display.



Screenshots from the Loading layers of the Interactive Map

INTERACTIVE MAP

On	Heater IDs
Off	RTD positions & IDs
Off	Loading: Bridge groups
Off	Loading: Notes
Off	Loading: Predicted glue layer thickness (based on shim test results)
Off	CMM: XY metrology (triplets)
Off	CMM: XY metrology (quads)
Off	CMM: Z metrology



Syringe ID 2021-A-12 Tuesday 4 May 2021-A-14 Wednesday 5 May 2021-A-15 Thursday 6 May 2021-A-16 Friday 7 May 2021-A-17

Heater ID label
Border color: Load date
Q: Quad heater
S: Singlet heater All singlet modules are Batch 2

p19-0 ring prototype - cooling tubes up

INTERACTIVE MAP

Off Heater IDs RTD positions & IDs Loading: Bridge groups Loading: Notes CMM: XY metrology (triplets) CMM: XY metrology (quads)


Off CMM: Z metrology For the p19-0 ring loading, we have two bridges. One bridge loads 2 quads at a time, and the other loads 3 singlets at a time (a triplet). Cuad pair positions:
- 0.9-0.10
- 0.1-0.2
- 0.3-0.4
- 0.5-0.6
- 0.7-0.8

- Triplet set positions:
 T9-T1-T2
 T3-T4-T5
 T6-T7-T8



Quad loading bridge (2 quad modules/load)


Triplet loading bridge (3 singlet modules/load)




Pipe position determines ring rotation

LEGEN	ND	
Load date	Syringe ID	
Monday 3 May	2021-A-12	
Tuesday 4 May	2021-A-14	
Wednesday 5 May	2021-A-15	
Thursday 6 May	2021-A-16	
Friday 7 May	2021-A-17	

All singlet modules are Batch 2



p19-0 ring prototype - cooling tubes up



Observations, properties, and measurements by Heater ID Properties

Quads

ater ID: Quads, batch	#1	#2	#3	#4	#5	#6	#7	#8	#9	#10	Uncertainty	Source	
-----------------------	----	----	----	----	----	----	----	----	----	-----	-------------	--------	--

Length (cm)	4.110	4.106	4.102	4.101	4.105	4.101	4.101	4.108	4.105	4.103	±30 m	Heaters.xlsx
Width (cm)	4.254	4.245	4.244	4.246	4.253	4.254	4.264	4.254	4.255	4.247	±30 m	Heaters.xlsx
Thickness (m)	310	310	315	312	312	315	312	312	312	312	±5 m	Heaters.xlsx
Resistance when wires first bonded ()	2.4	2.4	2.4	2.6	2.4	2.5	2.5	2.3	2.4	2.4	±0.1	Heaters.xlsx
Resistance: mounted on ring, before spray painting ()	2-3	2	2	2	2	2	2	2	2	2		Heaters.xlsx
Mass (g)									1.498	1.564	± 0.001 g	
Module thickness at center, measured with micrometers (m)									305	303	± 1 m	
Wire thicknesses, measured with calipers (mm)												

Triplets

Heater ID: Singles, batch	#1	#2	#3	#4	#5	#6	#7	#18	#9	Uncertainty	Source
Length (cm)										±30 m	Heaters.xlsx
Width (cm)										±30 m	Heaters.xlsx
Thickness (m)										±5 m	Heaters.xlsx
Resistance when wires first bonded ()	2.4	2.4								±0.1	Heaters.xlsx
Resistance: mounted on ring, before spray painting ()	2-3	2	2	2	2	2	2	2	2		Heaters.xlsx
Mass (g)										± 0.001 g	
Module thickness at center, measured with micrometers (m)										± 1 m	
Wire thicknesses, measured with calipers ()											

Heater visual inspection

Quads

Heater ID	#1	#2	#3	#4	#5	#6	#7	#8	#9	#10
Before IPA wash & dry rag polish										
After IPA wash & dry rag polish										
Comments									Particles across its surface. Nico tried to blow them off with an ion gun. No effect	Noticed a peculiar speck artifact. Did not come off with a single IPA cleaning. Appears to be Cu

Triplets

Heater ID	#1	#2	#3	#4	#5	#6	#7	#18	#9
Before IPA wash & dry rag polish									
After IPA wash & dry rag polish									
Comments									

Loading experience

Quads

Heater ID	#1	#2	#3	#4	#5	#6	#7	#8	#9	#10
Load date									2021-05-03	2021-05-03
Load position									Q9	Q10
Shim testing results										
Expected glue layer thickness (m)									~200	100-200
100-m shim									Pass	Pass
200-m shim									Fail	Pass
Glue batch										
Syringe ID	2021-A-14	2021-A-14	2021-A-14	2021-A-14	2021-A-15	2021-A-15	2021-A-15	2021-A-15	2021-A-12	2021-A-12
Dispensing										
Estimated glue mass per star (mg)									71	71

Averaged mass tests					2, 3, 4, 5	2, 3, 4, 5
Time elapsed since syringe fully thawed					64	64
Minutes module held under vacuum (Hold time)					Overnight	Overnight

Triplets

Heater ID	#1	#2	#3	#4	#5	#6	#7	#18	#9
Load date									
Load position									
Shim testing results									
Expected glue layer thickness (m)									
100-m shim									
200-m shim									
Glue batch									
Syringe ID									
Date dispensed									
Dispensing									
Estimated glue mass per star (mg)									
Averaged mass tests									
Time elapsed since syringe fully thawed									
Minutes module held under vacuum (Hold time)									

Metrology

Here is the link to the z measurements of the tube-up side of the 19-0 ring: $https://docs.google.com/spreadsheets/d/1-wvzPj9BKTd7p5U0iAwyJC_zR2qVB3EyFneJkcj2nHE/edit?usp=sharing$

Thermal imaging